



PRODUCT INFORMATION StepByStep-I_TY_US - 16.12.2021 - www.vsamerica.com

StepByStep-I Height-adjustable skid table

Frame of powder-coated steel tube with asymmetrically-positioned legs (cantilever) on steel skids with kicking protection. All steel tubes in round profile.
Table heights in 6 steps in accordance with DIN EN 1729. Height adjustment in steps with Allen-key or hand-wheel.

Tabletop made from laminated LIGNOpal chipboard with a seamlessly cast-on safety edge made from polyurethane (PUR). Optionally with an extremely robust LIGNOdur safety top with softly rounded waterfall edges.

Features of top. Fixed horizontal working surface.

Accessories and options. Glides for hard or soft floors or with 2 castors and 2 glides, and a book storage, plastic box or different kinds of chair suspension.

Important notice. The table height can vary slightly depending on the type of top and the glides. PUR edges are extremely robust, but can show signs of discoloration over time.

The following material groups are available to choose from: Frame made of steel tube: M1; Top made of LIGNOdur: L1; Top made of chipboard with PUR edge: L2.

Further products on this page: PantoSwing-LuPo.

		Table heights ($\pm 7/8$ inch) as per DIN EN 1729					
StepByStep I	LIGNOdur	d = 19 $3/4$ inch d = 19 $3/4$ inch		02904	02905		
	LIGNOpal-PUR	d = 25 $5/8$ inch w inch		02901		02993	02994
		Height adjustable in steps	29 $1/2$	27 $5/8$	51 $1/4$	29 $1/2$	51 $1/4$